

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An image processing apparatus comprising:
an image obtaining unit that obtains an image captured with an image sensor through an optical system; and
a defect information generating unit that generates defect information indicating a defect within the image having been obtained, based upon a value at a target pixel and an average value of a plurality of pixel values corresponding to pixels present within a predetermined range containing the target pixel, wherein:
~~the image sensor captures an image through an optical system; and~~
the defect information is information on a projected image of a defect within an optical path, which manifests in the ~~image~~ image,
the defect information generating unit simultaneously generates information indicating a position of the projected image of the defect within the optical path and information indicating intensity of the projected image of the defect within the optical path and records the position information and the intensity information, and
the defect information generating unit includes a relative ratio calculation unit that calculates a relative ratio of the value at the target pixel and the average value of the plurality of pixel values corresponding to the pixels present within the predetermined range containing the target pixel, and generates the defect information based upon the calculated relative ratio.
- 2.-4. (Canceled)
5. (Previously Presented) An image processing apparatus comprising:
an image obtaining unit that obtains an image captured with an image sensor;

a defect information generating unit that generates defect information indicating a defect within the image having been obtained, based upon a value at a target pixel and an average value of a plurality of pixel values corresponding to pixels present within a predetermined range containing the target pixel; and

a correction unit that corrects the defect within the image based upon the defect information, wherein:

the defect information generating unit includes a relative ratio calculation unit that calculates a relative ratio of the value at the target pixel and the average value of the plurality of pixel values corresponding to the pixels present within the predetermined range containing the target pixel, and generates the defect information based upon the calculated relative ratio; and

the correction unit corrects the defect by multiplying a value at a corresponding pixel by a reciprocal of the relative ratio.

6. (Canceled)

7. (Canceled)

8. (Currently Amended) An image processing apparatus comprising:

an image obtaining unit that obtains a reference image photographed through an optical system; and

a defect information generating unit that generates defect information indicating a defect within the reference image having been obtained, based upon a value of a target pixel and an average value of a plurality of pixel values corresponding to pixels present within a predetermined range containing the target pixel in the reference image, wherein:

the defect information is information on a projected image of a defect within an optical path, which manifests in the ~~image~~image.

the defect information generating unit simultaneously generates information indicating a position of the projected image of the defect within the optical path and information indicating intensity of the projected image of the defect within the optical path and records the position information and the intensity information, and

the defect information generating unit includes a relative ratio calculation unit that calculates a relative ratio of the value at the target pixel and the average value of the plurality of pixel values corresponding to the pixels present within the predetermined range containing the target pixel, and generates the defect information based upon the calculated relative ratio.

9. (Previously Presented) An image processing apparatus comprising:

an image obtaining unit that obtains a reference image photographed through an optical system; and

a defect information generating unit that generates defect information indicating a defect within the reference image having been obtained, based upon a value of a target pixel and an average value of a plurality of pixel values corresponding to pixels present within a predetermined range containing the target pixel in the reference image, wherein:

the defect information generating unit includes a relative ratio calculation unit that calculates a relative ratio of the value at the target pixel and the average value of the plurality of pixel values corresponding to the pixels present within the predetermined range containing the target pixel, and generates the defect information based upon the calculated relative ratio;

the image obtaining unit obtains a correction target image photographed through the optical system;

there is further provided a correction unit that corrects a defect within the correction target image based upon the defect information within the reference image; and

the correction unit corrects a value of a corresponding pixel in the correction target image by multiplying the value of the corresponding pixel with a reciprocal of the relative ratio calculated for the reference image.

10. (Currently Amended) An image processing apparatus according to claim 9,
~~comprising:~~

~~—— an image obtaining unit that obtains a reference image photographed through an optical system;~~

~~—— a defect information generating unit that generates defect information indicating a defect within the reference image having been obtained, based upon a value of a target pixel and an average value of a plurality of pixel values corresponding to pixels present within a predetermined range containing the target pixel in the reference image, wherein:~~

~~—— the image obtaining unit obtains a correction target image photographed through the optical system;~~

~~—— there is further provided a correction unit that corrects a defect within the correction target image based upon the defect information within the reference image; and~~

wherein: the correction unit determines a the correction value by using an initial signal value indicated at a specific correction target pixel position.

11. (Previously Presented) An image processing apparatus according to claim 9,
wherein:

if the reference image and the correction target image have been photographed through an optical system in substantially identical optical conditions with regard to an aperture value and a pupil position, the correction unit corrects a value at a pixel constituting the correction target image by directly using the defect information having been generated.

12. (Previously Presented) An image processing apparatus according to claim 9,
further comprising:

a defect information conversion unit that converts the defect information in correspondence to at least either of an aperture value and a pupil position constituting optical conditions of the optical system, wherein:

if the reference image and the correction target image have been photographed through the optical system under different optical conditions with regard to at least either the aperture value or the pupil position, the correction unit corrects a value at a pixel constituting the correction target image by using the converted defect information.

13.-18 (Canceled)

19. (Withdrawn) An image processing apparatus comprising:

an image obtaining unit that obtains an image captured by using an image sensor capable of separating light into a plurality of colors;

a luminance signal generating unit that generates a luminance signal based upon signals of the plurality of colors constituting the image;

a defect information generating unit that generates defect information indicating a defect within the image based upon the luminance signal for the image having been generated; and

a correction unit that corrects a value corresponding to a color component at a defective pixel within the image by using the defect information.

20. (Canceled)

21. (Withdrawn) An image processing apparatus according to claim 19, further comprising:

a defect information generating unit that generates defect information indicating a defect within the image having been obtained based upon a value indicated by the luminance signal generated for a target pixel and an average value among values indicated by luminance

signals generated for a plurality of pixels within a predetermined range containing the target pixel.

22. (Withdrawn) An image processing apparatus according to claim 21, wherein:
the defect information generating unit includes a relative ratio calculation unit that calculates a relative ratio of the value indicated by the luminance signal generated for the target pixel and the average value of the luminance signals generated for the plurality of pixels within the predetermined range containing the target pixel, and generates the defect information based upon the relative ratio having been calculated.

23. (Withdrawn) An image processing apparatus according to claim 21, further comprising:

a correction unit that corrects a value corresponding to a color component at a corresponding pixel by multiplying the value by a reciprocal of the relative ratio.

24.-36. (Canceled)

37. (Withdrawn) An image processing apparatus comprising:
an image obtaining unit that obtains a first image photographed through an optical system and a second image photographed under optical conditions different from optical conditions in which the first image is photographed; and

a defect information generating unit that generates defect information indicating a defect in the first image or the second image by using the first image and the second image, wherein:

the first image and the second image are photographed under different optical conditions with regard to at least either of an aperture value and a pupil position.

38. (Withdrawn) An image processing apparatus according to claim 37, further comprising:

a correction unit that corrects a defect in the first image or the second image by using the defect information.

39. (Canceled)

40. (Withdrawn) An image processing apparatus according to claim 37, wherein:
the defect information generating unit includes an optical condition conversion unit that converts at least either the first image or the second image so as to conform to a specific optical condition, in order to eliminate a mismatch of the optical conditions for the first image and the second image.

41. (Withdrawn) An image processing apparatus according to claim 40, wherein:
if the optical conditions with regard to the aperture value are different, the optical condition conversion unit executes low pass filter processing on a pixel signal generated based upon the first image or the second image so as to convert a defect state corresponding to the first image or the second image to a defect state estimated to manifest at a matching aperture value.

42. (Withdrawn) An image processing apparatus according to claim 41, wherein:
the optical condition conversion unit executes conversion by using a substantially uniformly weighted low pass filter.

43. (Withdrawn) An image processing apparatus according to claim 40, wherein:
if the optical conditions with regard to the pupil position are different, the optical condition conversion unit executes displacement processing through which a pixel signal generated based upon the first image or the second image is displaced from a center of an optical axis of the optical system along a direction of a radius vector so as to convert a defect state corresponding to the first image or the second image to a defect state estimated to manifest at a matching pupil position.

44. (Withdrawn) An image processing apparatus according to claim 43, wherein:
the optical condition conversion unit executes displacement processing through which a pixel signal located further away from the center of the optical axis is shifted to a greater extent along the radius vector.

45. (Withdrawn) An image processing apparatus according to claim 43, wherein:
the optical condition conversion unit executes the displacement processing by executing an arithmetic operation to predict an extent of displacement on an assumption that foreign matter causing the defect is present over a specific distance from an image-capturing surface within the optical system along the optical axis.

46. (Withdrawn) An image processing apparatus according to claim 37, wherein:
one of the first image and the second image is a correction target image to undergo correction and the other image is a reference image used to generate the defect information.

47. (Withdrawn) An image processing apparatus according to claim 37, wherein:
the first image and the second image are both correction target images to undergo correction; and

the defect information generating unit generates defect information to be used commonly in conjunction with the first image and the second image by using the first image and the second image.

48. (Withdrawn) An image processing apparatus according to claim 47, wherein:
the defect information generating unit includes an optical condition conversion unit that converts at least either the first image or the second image so as to conform to a specific optical condition, in order to eliminate a mismatch of the optical conditions for the first image and the second image.

49. (Withdrawn) An image processing apparatus according to claim 46, wherein:
the image obtaining unit obtains the reference image photographed at an aperture value corresponding to a narrowest aperture opening setting in an adjustable aperture value range of the optical system.

50. (Withdrawn) An image processing apparatus according to claim 37, wherein:
the defect information generating unit generates defect information indicating a defect within the image having been obtained, based upon a value of a target pixel and an average value of a plurality of pixel values corresponding to pixels present within a predetermined range containing the target pixel in the image.

51. (Withdrawn) An image processing apparatus according to claim 46, wherein:
the image obtaining unit obtains a reference image photographed within a predetermined period of time preceding or following a time point at which the correction target image is photographed.

52. (Withdrawn) An image processing apparatus comprising:
an image obtaining unit that obtains a first image photographed through an optical system and a second image photographed under optical conditions different from optical conditions in which the first image is photographed; and
a correction unit that corrects a defect contained within the first image or the second image by using the first image and the second image, wherein:

the first image and the second image are photographed under different optical conditions with regard to at least either of an aperture value and a pupil position.

53. (Canceled)

54. (Withdrawn) An image processing apparatus comprising:
an image obtaining unit that obtains a photographic image captured with an image sensor;

a flat portion extraction unit that extracts a flat portion area within the photographic image having been obtained; and

a defect information generating unit that generates defect information corresponding to the extracted flat portion area.

55. (Withdrawn) An image processing apparatus according to claim 54, further comprising:

a correction unit that corrects an image within the flat portion area based upon the defect information.

56. (Withdrawn) An image processing apparatus according to claim 54, wherein:
the defect information corresponding to the flat portion area is generated based upon a value at a target pixel and an average value of a plurality of pixel values corresponding to pixels present within a predetermined range containing the target pixel in the image within the flat portion area.

57. (Withdrawn) An image processing apparatus according to claim 56, wherein:
the defect information generating unit includes a relative ratio calculation unit that calculates a relative ratio of the value at the target pixel and the average value of the plurality of pixel values corresponding to the pixels present within the predetermined range containing the target pixel, and generates the defect information corresponding to the flat portion area based upon the calculated relative ratio.

58. (Withdrawn) An image processing apparatus according to claim 55, further comprising:

a relative ratio calculation unit that calculates a relative ratio of a value at a target pixel and an average value of pixel values corresponding to a plurality of pixels present within a predetermined range containing the target pixel, among pixels constituting an image of the flat portion area, wherein:

the defect information generating unit generates the defect information corresponding to the flat portion area based upon the relative ratio having been calculated; and

the correction unit uses a reciprocal of the relative ratio corresponding to a pixel in the image of the flat portion area when correcting a value of the corresponding pixel in the image of the flat portion area by multiplying the pixel value by the reciprocal.

59. (Withdrawn) An image processing apparatus according to claim 58, wherein:

the correction unit executes low pass processing on the relative ratio which has been generated as the defect information and corrects the value of the corresponding pixel in the image of the flat portion area by multiplying the pixel value by a reciprocal of the relative ratio having undergone the low pass processing, which corresponds to the pixel in the image of the flat portion area.

60. (Withdrawn) An image processing apparatus according to claim 54, wherein:

the flat portion extraction unit executes edge extraction within the photographic image and extracts an area in which no edge is extracted as a flat portion area.

61. (Withdrawn) An image processing apparatus according to claim 54, wherein:

the flat portion extraction unit includes a gradation conversion unit that executes gradation conversion on the photographic image and executes a flat portion area extraction on the photographic image having undergone the gradation conversion.

62. (Withdrawn) An image processing apparatus according to claim 61, wherein:

when gradation of the photographic image is indicated with a linear signal, the gradation conversion unit converts the linear signal to a nonlinear signal and executes conversion by enlarging the gradation on a low intensity side and compressing the gradation on a high intensity side.

63. (Canceled)

64. (Withdrawn) An image processing apparatus according to claim 62, wherein:
the gradation conversion unit executes conversion by using a square root function.

65. (Canceled)

66. (Withdrawn) An image processing apparatus according to claim 60, wherein:
the edge extraction is executed by calculating differences corresponding to a plurality
of distances between a target pixel and surrounding pixels along a plurality of directions.

67. (Withdrawn) An image processing apparatus according to claim 55, further
comprising:

a luminance level decision-making unit that makes a decision as to whether or not a
luminance level of the photographic image is equal to or higher than a predetermined
luminance level, wherein:

the correction unit executes correction for an area determined to be a flat portion area,
where the luminance level is equal to or greater than the predetermined level.

68. (Withdrawn) An image processing apparatus according to claim 54, further
comprising:

a reference image obtaining unit that obtains a reference image captured with the
image sensor; and

a reference image defect information generating unit that generates defect information
corresponding to the reference image, wherein:

the defect information generating unit generates the defect information corresponding
to the flat portion area by using area information included in the defect information for the
reference image and area information corresponding to the flat portion area in combination.

69. (Withdrawn) An image processing apparatus according to claim 68, wherein:

if an area that is not extracted as the flat portion area is still indicated to be a defect area by the defect information for the reference image, the flat portion extraction unit extracts the defect area as a flat portion area.

70. (Withdrawn) An image processing apparatus according to claim 68, wherein:
the defect information generating unit generates the defect information for an area indicated as a defect area by the defect information for the reference image and also determined to be the flat portion area.

71. (Withdrawn) An image processing apparatus according to claim 68, further comprising:

a defect information conversion unit that converts the defect information for the reference image to defect information equivalent to defect information for a reference image photographed under optical conditions identical to optical conditions under which the photographic image has been photographed when the photographic image and the reference image have been photographed under different optical conditions, wherein:

the defect information generating unit uses the defect information for the reference image resulting from the conversion.

72. (Withdrawn) An image processing apparatus according to claim 69, further comprising:

a defect information conversion unit that converts the defect information for the reference image to defect information equivalent to defect information for a reference image photographed under optical conditions identical to optical conditions under which the photographic image has been photographed when the photographic image and the reference image have been photographed under different optical conditions, wherein:

the flat portion extraction unit uses the defect information for the reference image resulting from the conversion.

73. (Withdrawn) An image processing apparatus according to claim 72, wherein:
in consideration of an error in defect information conversion executed by the defect information conversion unit, the defect information generating unit expands the defect area indicated by the defect information for the reference image, at least by an extent corresponding to the error in the defect information conversion.

74. (Withdrawn) An image processing apparatus according to claim 54, wherein:
the image obtaining unit obtains a plurality of photographic images captured with the image sensor;

the flat portion extraction unit extracts the flat portion area in each of the plurality of photographic images; and

the defect information generating unit generates defect information corresponding to the flat portion area in one of the plurality of images by using images of flat portion areas in the plurality of images having been extracted.

75. (Withdrawn) An image processing apparatus according to claim 54, wherein:
the image obtaining unit obtains a plurality of photographic images captured with the image sensor;

the flat portion extraction unit extracts the flat portion area in each of the plurality of photographic images; and

the defect information generating unit generates defect information corresponding to an entire image of each of the plurality of images by using images of flat portion areas in the plurality of images having been extracted.

76. (Withdrawn) An image processing apparatus according to claim 75, wherein:
the defect information corresponding to the flat portion area is generated based upon a value at a target pixel and an average value of a plurality of pixel values corresponding to

pixels present within a predetermined range containing the target pixel in the image within the flat portion area.

77. (Withdrawn) An image processing apparatus according to claim 76, wherein:
the defect information generating unit includes a relative ratio calculation unit that calculates a relative ratio of the value at the target pixel and the average value of the plurality of pixel values corresponding to the pixels present within the predetermined range containing the target pixel, and generates the defect information corresponding to the flat portion area based upon the calculated relative ratio.

78. (Withdrawn) An image processing apparatus according to claim 69, wherein:
if there are a predetermined number of pixels or more pixels from which an edge has been extracted are present around the defect area indicated by the defect information for the reference image, the flat portion extraction unit does not extract the defect area as the flat portion area.

79. (Withdrawn) An image processing apparatus according to claim 78, wherein:
if an edge has been extracted from a majority of pixels among pixels present in a predetermined area surrounding a pixel in the defective area, the flat portion extraction unit does not extract the pixel in the defect area as a pixel in the flat portion.

80. (Previously Presented) A computer-readable computer program product having an image processing program enabling a computer to execute functions of an image processing apparatus according to claim 1.

81. (Canceled)

82. (Canceled)

83. (Currently Amended) An image processing apparatus according to ~~claim~~
~~82~~claim 1, wherein:

the defect information generating unit generates defect information for an area within the image, which satisfies a predetermined condition.

84. (Canceled)

85. (Currently Amended) An image processing apparatus according to ~~claim~~
~~84~~claim 8, wherein:

the relative ratio calculation unit sets the calculated relative ratio to 1 if the calculated relative ratio falls within a predetermined range containing 1.

86. (Previously Presented) An image processing apparatus according to claim 85, wherein:

the relative ratio calculation unit correlates the predetermined range over which the calculated relative ratio is set to 1 with a standard deviation value of the calculated relative ratio.

87. (Previously Presented) An image processing apparatus according to claim 86, wherein:

the relative ratio calculation unit sets the predetermined range over which the calculated relative ratio is set to 1 to a $\pm (3 \times \text{standard deviation value})$ range.

88. (Withdrawn) A computer-readable computer program product having an image processing program enabling a computer to execute functions of an image processing apparatus according to claim 37.

89. (Withdrawn) A computer-readable computer program product having an image processing program enabling a computer to execute functions of an image processing apparatus according to claim 54.